

## ***Multi-Function Video Test Monitor***



### *Video Test Monitor*

## ***4KTESTMON***

- > Designed for installation and maintenance of IP and Analog cameras
- > Composite video (CVBS, TVI, CVI, AHD) and IP video input support
- > 7" Retina Touch-Screen, 1920 x 1200 resolution
- > H.265 & H.264 standards support, up to 4K resolution
- > RJ45 Ethernet cable, video level meter and cable trace test support
- > PoE power voltage, PING and IP address searching support
- > HDMI input and output
- > ONVIF Profile S Compliant
- > Rechargeable lithium battery and external 12VDC power supply
- > Wi-Fi connectivity support
- > Audio, PTZ control and color bar generator support

## Specifications

Video Test Monitor	
Monitor	7" retina touch screen
IP Video	1 - RJ-45, 10M/100M auto adjust
Analog Video	1 x BNC input: CVBS, TVI, CVI, AHD 1 x BNC output
Serial Interface	1 x RS-485
HDMI	1 x input and 1 x output
PoE	1 x RJ45, 48V output, maximum 24W
Camera Power	12VDC, 2A output power to camera
Audio	1 x RCA input and 1 x RCA output
Micro SD Slot	8GB card included
Power Supply	12VDC, 2A
Operating Temperature	-10°C ~ + 50°C (4°F ~ 122°F)
Operating Humidity	30% ~ 90% RH
Dimensions	255 x 160 x 46mm (10 × 6.3 × 1.8")
Weight	.95kg (2.1lb)

Top View



Bottom View

