


16ch, 16 PoE, 12MP Resolution, H.265 NVR



16ch NVR

NR16P2

- > 16ch network recorder with H.265 Compression for Best-in-Class Recording and Storage Performance
- > Embedded PoE Switch for all Video Channels Up to 240W
- > Supports recording of up to 12MP (4000 x 3000) Resolution Images
- > Display Images up to 4k (3840 x 2160) Resolution on HDMI Output
- > Concurrent Display on HDMI and VGA Monitor Outputs
- > Easy Plug and Play Functionality with Automatic Device Discovery and Display
- > Supports 2 SATA HDD's up to 10TB each for 20TB total
- > ONVIF Profile Series Compliant
- > Powerful Video Content Analysis Features such as Cross Line Detection, Audio Detection, Scene Change, People Counting
- > Supports Various Fisheye Camera Dewarping Modes for Live View and Playback Through GUI and VMS Software
- > Supports Cloud Upgrade for NVR and Cameras, with Automatic Detection of Latest Firmware and Upgrades
- > Supported by uniview tec Guard Station Client Software and Guard Viewer Mobile App's for iPhone and Android Devices
- > Long Range PoE Capability, up to 250M (825ft) with Cat5E or Cat6


NR16P2 16ch NVR

Network Recorders

Specifications

| Video | |
|---------------------------------|--|
| IP Camera Inputs | 16 channels |
| Video Formats | Ultra 265, H.265, H.264 |
| Recording Video Resolution | 12MP Maximum |
| Playback Video Capability (fps) | 3 x 12MP @ 25; 4 x 4K @ 30; 8 x 4MP @ 30; 16 x 1080P @ 30 |
| Monitor Output | 1 x HDMI (4K~ 720p); 1 x VGA (1080p ~ 720P) |
| Synchronous Playback | 16 channels |
| Network | |
| Protocols | P2P, UPnP, NTP, DHCP, PPPoE |
| Bandwidth | Incoming – 160Mbps; Outgoing – 320Mbps |
| Remote Users | 128 |
| Video Analytics | Detection: Face, Intrusion, Cross line, Audio, Defocus, Scene Change, Auto tracking, People Counting, Face and Behavior Search |
| General | |
| Network Interface | 1 – RJ45, 10M/100M/1000M, Ethernet |
| USB Interface | Front panel: 1 x USB2.0, Rear panel: 1 x USB3.0 |
| Alarm Interface | 4ch – Inputs; 1ch - Output |
| PoE Interface | 16 – 100Mbps RJ45 ports; IEEE 802.3af/at; Max 30W single port, w/ Max 240W total |
| Audio Interface | 1ch RCA Input / Output |
| Corridor Mode | Record / Playback Multiple Cameras Simultaneously |
| Hard Disk | 2 SATA, up to 10TB each, total 20TB |
| Power | 100-240VAC; 20W Consumption (w/o HDD) |
| Operating Temperature | -10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH(non-condensing) |
| Rack Mountable | Yes; Ears available upon request |
| Dimensions (WxDxH) | 380 × 315 × 46 mm (15 × 12.4 × 1.8") |
| Weight (w/o HDD) | 2.48kg (5.47lb) |
| Conformity Certifications | FCC, CE (UL – Power Supply only) |

Dimensions



Accessories

XDLBB2 NVR Lockbox

Models

NR16P2-2T NR16P2-4T
NR16P2-8T NR16P2-16T