8-Port PoE Network Switch



PoE Switch **NSW081P**

- > 8 x 100Mbps RJ45 PoE ports
- > 2 x 100Mbps RJ45 Network ports
- > Support buffer optimization and port traffic control
- > Multiple working modes to address all applications: Normal, Secure and Surveillance
- > PoE complies with IEEE802.3af/at, up to 30W for single port
- > Up to 825ft (250m) transmission distance on EXTEND mode
- > High quality, metal housing





Specifications

PoE Network Switch	
Ports	8 × 100Base-TX RJ45 PoE ports 2 x 100Base-TX RJ45 Network ports
Standards	IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at
MAC	8К
Packet Forwarding Rate	1.498Mpps
Switching Capacity	2Gbps
Work Modes	Default (Normal mode): All ports can communicate with each other. VLAN (Secure mode): Downlink ports can communicate only
	with uplink ports.
	EXTEND (Surveillance mode): Transmission distance up to 250 meters.
Indicator LED's	PWR:
	Steady on: AC input is normal;
	Off: No AC input
	PoE:
	Off: No PoE power supply;
	Steady on: PoE power supply is normal
	Flashing: PoE power supply is abnormal
	LINK/ACT:
	Off: No link
	Steady: Linked at 10/100Mbps
	Flashing: Transmitting data
PoE	802.3at/af; Max capacity for single port = 30W
	Max PoE capacity: 120W
AC Voltage	100-240V, 50/60Hz
Operating Temperature	0°C-40°C (32°F-104°F)
Operating Humidity	10% ~ 95% RH
Dimensions	160 x 93 x 32mm (6.3 × 3.7 × 1.3")
Weight	1.22kg (2.7lb)

Uniview Technology / 850 Freeport Pkwy, Ste. 100, Coppell, TX 75019 Toll Free: 888-288-7644 / Main 972-459-8645 / Fax 972-459-8661



©2020 uniview **t**ec All rights reserved. Specifications and Design are subject to change without notice. **UVT6311118-01**