

8MP, COLORHUNTER+ (Wise-ISP), WDR, BULLET



Fixed Lens Bullet

IPB4KW128X

- > Fully Adheres to National Defense Authorization Act (NDAA) Guidelines
- > ColorHunter+ (Wise-ISP) technology ensures ultra-high color image up to 0.0003 Lux
- > Exceptional Video Quality with 8MP, 3840 x 2160 Resolution
- > H.265 Video Compression for Drastically Reduced Bandwidth and Storage Requirements
- > Powerful White Light Operation up to 98 Feet
- > 2.8mm Fixed Lens; ONVIF Profile S Compliant
- > Exceptional Night Time Color Image and WDR functionality
- > Dual Video Streams, Built-in mic, Smart Illumination, Digital Defog and 3D DNR
- > Intelligent, smart intrusion prevention technology for significantly reduced false alarms when focusing on humans and motor vehicles
- > PoE & 12VDC Power Options and Optional Wall and Pendant Mounts Available
- > Built-in Micro-SD Card Slot enables local storage up to 512GB
- > 3-Way Axis, CE and IP67 Weather Resistant
- > Supported by uniview tec Guard Station Software, as well as Guard Live and Guard Viewer Mobile App's for iPhone and Android Devices

www.univiewtechnology.com

uniview tec

UVT70660625-00


Specifications

Camera	Description
Max Resolution	8MP
Sensor	1/1.8" CMOS
Min. Illumination	Color : 0.0003 lux (F1.0, AGC ON)
Shutter	Auto/Manual, 1 ~ 1/100000s
Adjustment Angle	Pan: 0° ~ 360°, Tilt: 0° ~ 90°, Rotate: 0° ~ 360°
S/N	>52dB
WDR	120dB
Lens	Description
Focal Length	2.8mm
Iris Type	Fixed
Iris	F1.0
Field of View (H)	111.0°
Field of View (V)	63.0°
Field of View (D)	131.0°
DORI	Description
DORI Distance(Detect)	63.0m (206.7ft)
DORI Distance(Observe)	25.2m (82.7ft)
DORI Distance(Recognize)	12.6m (41.3ft)
DORI Distance(Identify)	6.3m (20.7ft)
Illuminator	Description
Illumination Distance(Warm Light)	30m (98ft)
Light On/Off Control	Auto/Manual
Video	Description
Video Compression	H.265; H.264; MJPEG
H.264 Code Profile	Baseline profile, Main profile, High profile
Frame Rate	<u>Main Stream</u> : 4MP (2560*1440) @30fps; 1080P @30fps; 720P @30fps; D1 (720*576) @30fps; 640*360 @30fps; 2CIF (704*288) @30fps; CIF (352*288) @30fps; <u>Sub Stream</u> : 1080P @30fps; 720P @30fps; D1 (720*576) @30fps; 640*360 @30fps; 2CIF (704*288) @30fps; CIF (352*288) @30fps;
Video Bit Rate	128 Kbps ~ 6144 Kbps
U-code	Support
OSD; Privacy Mask	Up to 4
ROI	Up to 8
Video Stream	Dual Streams
Image	Description

White Balance	Auto; Outdoor; Fine Tune; Sodium Lamp; Locked; Auto2
Digital Noise Reduction	2D/3D DNR
Smart Illumination	Support
Flip	Normal; Flip Vertical; Flip Horizontal; 180°; 90°Clockwise; 90°Anti-clockwise
Dewarping	N/A
HLC	Support
BLC	Support
Defog	Digital Defog
Events	Description
Basic Detection	Cross-Line; Intrusion (based on human body detection); Motion Detection; Ultra Motion Detection; Tampering Alarm; Audio Detection
General Function	Watermark; IP Address Filtering; Access Policy; ARP Protection; RTSP Authentication; User Authentication; HTTP Authentication
Audio	Description
Audio Compression	G.711U; G.711A
Audio Bitrate	64 Kbps
Two-way Audio	N/A
Suppression	Support
Sampling Rate	8KHZ
Storage	Description
Edge Storage	Micro SD, up to 512 GB
Network Storage	ANR; NAS (NFS)
Network	Description
Protocols	IPv4; IPv6; IGMP; ICMP; ARP; TCP; UDP; DHCP; PPPoE; RTP; RTSP; RTCP; DNS; DDNS; NTP; FTP; UPnP; HTTP; HTTPS; SMTP; 802.1x; SNMP; QoS; RTMP; SSL/TLS
Compatible Integration	ONVIF (Profile S, Profile G, Profile T); API; SDK
User/Host	Up to 32 users, 2 user levels: administrator and common user
Security	Password Protection; Strong Password; HTTPS Encryption; Export Operation Logs; Basic and digest authentication for RTSP; Digest authentication for HTTP; TLS 1.2; WSSE and digest authentication for ONVIF
Client	Guard Live, Guard Viewer, Guard Station
Web Browser	Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above; Plug-in free live view: Chrome 57.0 and above, Firefox 58.0 and above, Edge 16 and above
Interface	Description
Audio I/O	N/A
Alarm I/O	N/A
Serial Port	N/A
Built-in Mic	Support
Built-in Speaker	N/A
Network	1 x RJ45 10M/100M Base-TX Ethernet

Certification	Description
EMC	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035) FCC (FCC 47 CFR part15 B)
Safety	CE LVD (EN 62368-1); UL/CUL (UL 62368-1, CAN/CSA C22.2 No. 62368-1)
Environment	CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU)
Protection	IP67 (IEC 60529); IK10 (IEC 62262)
General	Description
Power	DC 12V±25%, PoE (IEEE 802.3af); Power consumption: Max 3.9W
Power Interface	Ø 5.5mm coaxial power plug
Dimensions	206 × 73 × 73mm (8.1" × 2.9" × 2.9")
Weight	0.48kg(1.06lb)
Material	Metal
Environment	-30 °C ~ 60 °C (-22 °F ~ 140 °F), Humidity: ≤95% RH (non-condensing)
Surge Protection	4KV
Reset Button	Support

Dimensions



Accessories

See Camera Accessories Guide